

**EXTENDED RANGE
PERFORMANCE**

UltraForce® 350

COMPACT ELECTRO-OPTICAL AIRBORNE GIMBAL



APPLICATIONS

- COUNTER DRUG
- HOMELAND SECURITY
- PATROL
- SURVEILLANCE
- RECONNAISSANCE
- SEARCH AND RESCUE

FEATURES

- Lightweight high stiffness composite body
- Multiple Fields of View (FOV) 3-5µm thermal imagers
- Daylight colour camera with 26x zoom
- Spotter options
- Laser options
- 4-axis active stabilisation
- EASA Certified installations
- Simplified integrations
- Optimised usability
- It's all FLIR inside

BENEFITS

- Reduces weight for increased mission range
- Large format 640 x 512 infrared camera with extended performance optics allows for positive target analysis at safe stand-off ranges in all weather conditions
- Maximises standoff range and target acquisition during daytime surveillance missions; the low light function extends operation into dawn or dusk
- Identify targets at longer stand-off ranges during daytime surveillance missions; low light camera option provides extended operation into dawn and dusk
- Covertly determine target distance and location
- Outstanding stability ensures stable imagery by compensating for aircraft movement and vibration, critical for long range imaging
- The system can be delivered with EASA Form 1 certification
- Two Line Replaceable Unit (LRU) configuration and universal mounting interface with integrated quick disconnect is compatible with existing FLIR products
- Backlit and NVG compatible remote controller for 24/7 operation in the modern cockpit; integrated multi-mode auto-tracker to track moving or stationary targets
- FLIR controls the entire supply chain for the critical technology inside its Ultra class gimbals, ensuring fast service and long-term support.





UltraForce® 350

OVERVIEW

Gimbal size	350 mm (D) x 485 mm (H)
Gimbal weight	28 kg
Environmental	RTCA DO-160E

THERMAL IMAGING PERFORMANCE

Sensor type	3rd gen 640 x 512 3-5 µm focal plane array
Image Enhancements	Non Uniformity Correction Bad Pixel Replacement AGC (Automatic Gain Control) Histogram Equalisation Digital Details Enhancement (Tunable)
FOVs	
Wide	17.3° x 13.6°
Medium	5° x 4°
Narrow	1.2° x 0.9°
Ezoom	2x

DAYLIGHT IMAGING PERFORMANCE

Sensor	Super HAD Color
Resolution	740 000 pixels (PAL) 630,000 pixels (NTSC)
Fields of view	42° to 1.6° optical continuous zoom
Low light level	Without IR cut-off filter
Ezoom	2x

SPOTTER SCOPE OPTION

	COLOUR	LLTV
Sensor type	Colour CCD	EMCCD
Field of view	11.9° to 0.54° continuous zoom	15.8° to 0.72° continuous zoom
Sensitivity	1.5 Lux	<100 µLux

GIMBAL SPECIFICATIONS

LOS Pan range	360 degrees continuous
LOS Tilt range	+20 / -120 degrees
AZ/EL slew rate	Up to 60°/s
Stow	Magnetically held in stow position

ELECTRONICS CONTROL UNIT

Hand Controller Unit	0.8 kg, 230 mm Height
----------------------	-----------------------

INTERFACES

ARINC 429, RS232/422 and other interfaces to support navigation systems, moving maps, radars, searchlights, and GPS

OUTPUTS

Video	RS-170, NTSC, PAL, CCIR
-------	-------------------------

POWER

Power requirements	22-30 VDC < 150 W
--------------------	-------------------

OPTIONS

Auto-tracker, Laser Range Finder, Laser Pointer, longwave infrared camera, Control Unit (IFU)

CORPORATE HEADQUARTERS

FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 800.727.3547

BOSTON

FLIR Systems, Inc.
25 Esquire Road
North Billerica, MA 01862
PH: +1 800.464.6372

HUNTSVILLE

FLIR Systems, Inc.
Huntsville, AL USA
PH: +1 256.325.3547

PITTSBURGH

FLIR Systems, Inc.
Freeport, PA USA
PH: +1.724.295.2880

WASHINGTON, D.C.

FLIR Systems, Inc.
2800 Crystal Drive, Suite 330
Arlington, VA 22202 USA
PH: +1 703.416.6666

EUROPE

FLIR Systems Ltd.
West Malling, Kent
United Kingdom
PH: +44.1732.220011

CANADA

FLIR Systems Ltd.
Burlington, ON
Canada
PH: +1 800.613.0507

SWEDEN

FLIR Systems AB
Täby, Sweden
PH: +46.8.753.2500

MIDDLE EAST

FLIR Systems Middle East, FZCO
Dubai Airport Free Zone
PH: +9714.299.6898

www.flir.com/GS

